

MAXIGEAR S 75W-80

Full Synthetic Long-Life Transmission Oil

Description

Maxigear S 75W-80 is a high performance, all seasons extreme pressure synthetic gear oil developed for buses and heavy duty vehicles with ZF gear box.

Applications

Maxigear S 75W-80 is developed for buses and commercial vehicles operating under extremely heavy duty, where particularly long oil change intervals are recommended, for use in ZF gear boxes with or without interarder systems.

Benefits

- Very good aging resistance provides a long life between oil changes.
- Very high protection against corrosion.
- Excellent lubrication and wear prevention.
- Super extreme pressure characteristics.
- Perfect temperature-viscosity compatibility ensured with the smart oil technology.
- Very low pour point reduces wear at initial operation, and provides fuel savings.

Performance

API GL-4, MIL-L-2105, MAN 341 Type Z3, MAN 341 Type Z4, ZF TE ML-02L/16K, DAF, IVECO, RENAULT, Volvo 97307, ZF TE-ML 01L, ZF TE-ML 08, ZF TE-ML 13, ZF TE-ML 24A, Eaton Europe (300,000 km or 3 years)

Typical Specifications*

SAE Viscosity Grade		75W-80
Density, @ 15 °C, kg/m ³	ASTM D-4052	0,860
Flash Point, COC, °C	ASTM D-92	230
Viscosity, 40 °C, mm ² /s	ASTM D-445	51,75
Viscosity, 100 °C, mm ² /s		8,9
Viscosity Index	ASTM D-2270	153
Pour Point, °C	ASTM D- 97	-39

* Values shown may differ between productions.



Petrol Ofisi