

MAXIMA CX 0W-30

Long-Lasting Synthetic Motor Oil

Description

It is a next-generation motor oil formulated with synthetic base oils and special additives and produced for vehicles with emission-reducing systems containing DPF and SCR.

Applications

Developed for vehicles that require a motor oil at the performance level of ACEA C2 and FIAT 9.55535-DS1/9.55535-GS1 in next-generation diesel and gasoline engines. It can also be used in vehicles requiring motor oil at the performance level of ACEA C3.

Characteristics and Benefits

- Provides product optimization in large vehicle fleets of different brands.
- Ensures high engine performance.
- Extends the life of exhaust emission systems.
- Protects the environment by contributing to low emission production.
- Helps keep the engine clean by reducing deposit and sediment formation.
- Supports fuel efficiency.

Performance

ACEA C2, FIAT 9.55535-DS1/9.55535- GS1

Typical Specifications*

SAE Viscosity Grade		0W-30
Density, @ 15 °C, kg/m ³	ASTM D-4052	0.843
Flash Point, COC, °C	ASTM D-92	238
Viscosity, 40 °C, mm ² /s	ASTM D 445	64.1
Viscosity, 100 °C, mm ² /s		11.6
Viscosity Index	ASTM D-2270	178
Pour Point, °C	ASTM D-97	-39

* Values shown may differ between productions.